PILFER RESISTANT SOFTWARE PACKAGE

BACKGROUND OF THE INVENTION

The present invention relates to a software package, and more particularly to a pilfer resistant software package for a diskette and for printed instructions concerning the software.

Presently, software is packaged in a variety of ways, including the provision of the stored software medium and any instructions relating thereto in a carton which may be easily opened for viewing by a perspective customer. With such access to the elements of the package, pilferage becomes a problem.

SUMMARY OF THE INVENTION

It is the object of the present invention to provide a software package in which the instructions and related information are easily viewed by a perspective cus- 20 tomer, while at the same time the software and its related information are protected against pilferage.

According to the invention, the above object is achieved in a folded software container having a first ing the related information. Both sections share a common base which is preferably a polyvinylchloride (PVC) coated paperboard. Each of the storage sections comprises a molded, preferably clear, PVC cover which is welded to the base by radio frequency (RF) 30 welding.

The first storage section comprises a formed pocket for holding, for example, a diskette structure, and includes a slit extending between a pair of scorings which provide frangible locations whereby the diskette may be removed upon lifting the material at the slit to break the scorings. A molded bubble also extends between the scorings spaced from the slit and acts as a hinge for the flap which is formed after the scorings have been broken. The second storage section comprises a clear sheet having slots therein for a variety of purposes. First of all, simple instructions may be printed on the base for viewing through the clear plastic sheet. As an alternative, a separate printed sheet may be introduced between the base and the clear plastic sheet by way of one of the aforementioned slots. More detailed instructions and related material, in the form of a booklet, may be included when the clear plastic sheet is formed with a recess for receiving the book with its back cover ex- 50 tending through one of the slots. In this latter variation, the back cover may be glued to the base as a guard against pilferage.

According to another feature of the invention, the folded container comprises, for each section, a hollow 55 upstanding peripheral edge shaped to mate with the similar peripheral edge of the other section. One of the sections further comprises at least one projection of the hollow structure to mate with at least one recess of the other hollow structure with the projection and the re- 60 cess each including resilient bypassing hook walls for releasable engagement as a latch structure for holding the folded container in a closed condition.

BRIEF DESCRIPTION OF THE DRAWING

Other objects, features and advantages of the invention, its organization, construction and operation will be best understood from the following detailed description, taken in conjunction with the accompanying drawing, on which:

FIG. 1 is a perspective view of a software container constructed in accordance with the present invention;

FIG. 2 is a sectional view taken substantially along the line II—II of FIG. 1;

FIG. 3 is a sectional view, again basically along the line II-II of FIG. 1, but showing the container in a closed condition;

FIG. 4 is a perspective view illustrating the first storage section after the software storage pocket has been opened for access to the storage medium;

FIG. 5 is a sectional view taken substantially along the line V-V of FIG. 1; and

FIG. 6 is a fragmentary sectional view illustrating the latch condition of the software package in a closed condition.

DESCRIPTION OF THE PREFERRED **EMBODIMENTS**

Referring to the drawing, a software package constructed in accordance with the present invention is generally illustrated at 10 as comprising a first storage section 12 and a second storage section 14 connected section housing the software and a second section hous- 25 together by a hinge 16. The storage sections 12, 14 share a common base 18 which may comprise, for example, PVC coated paperboard. The hinge 16 comprises a pair of embossments 20 and 22 to facilitate folding of the package in the manner illustrated in FIG. 3.

As best seen in FIGS. 1 and 2, the storage section 12 comprises a molded sheet 24 which includes an upstanding peripheral edge 26 and a, in this case, shallow pocket 28 for holding a diskette structure, hereinafter simply termed diskette. As is known, a diskette comprises a storage disk housed in, conventionally, a paper container and may further include an envelope for the paper container. Of course, with proper dimensioning of the package and pocket, various magnetic tape cassettes and cartridges could be accommodated in the pocket 28.

The peripheral edge 26, as best seen in FIG. 2, comprises a stairstep structure including a pair of walls 30 and 34 and a pair of walls 32 and 36 connecting the walls 30 and 34 and for providing mating to a complemental structure of the storage section 14, as will be set forth below. The peripheral edge 26 also comprises a pair of projections 38 and 40 for the purpose of latching, as will be discussed in connection with FIG. 6, and a plurality of projections 42, 44 and 46 which aid in aligning the stairstep structures when the package is closed.

The pocket 28 comprises a transverse slit 48 (later to form an edge 48') which is connected, so to speak, with a bubble 62 by way of a plurality of scores 50, 52, 54, 56, 58 and 60 (later to form edges 50', 52', 54', 56', 58',60') of which the latter two scores include sections extending into the bubble 62. The bubble 62 also comprises an aperture 64 therethrough. A diskette 66 is located and sealed in the pocket 28. As best seen in FIG. 4, access may be had to the diskette 66 by lifting the, as viewed, upper edge of the slot 48 to break the scores and form a flap 68 which is hinged by the material of the bubble between the scores 58, 60 and the aperture 64. This frangible structure is a deterrent to pilferage.

The storage section 14 is provided for information 65 concerning the software stored in the storage section 12 and comprises a molded sheet, preferably a clear PVC sheet 70 comprising, again, an upstanding peripheral edge 72 having a stairstep configuration. This stairstep